

SOLAR LIGHTING TOWER GP65K URBAN



Globe Power's GP65K Urban Solar Lighting Tower has been built to suit various industries and is compliant with both metropolitan and mining specifications.

- 7 day timer
- Day/night modes
- Jack pads
- Audio safety message
- Fire extinguisher
- Emergency stop
- Isolators
- Tilt sensor
- AC charger
- Wheel chocks
- Tie down points
- Lifting points



USER-FRIENDLY OPERATION INTERFACE

SOLAR

PORTABLE & EASY TO TRANSPORT

AUSTRALIAN DESIGNED & ENGINEERED

PRODUCT SPECIFICATIONS

GENERAL

Model	GP65K Urban
Lumen Output	68,000
Mast Height	30 feet
Mast Type	Hydraulic/Cable
Lights	4 x 150w LED Modules (Dimmable)
Coverage	106,850ft ² at 5 lux

OPERATIONAL DATA

Wind Rating	62mph
Working Temperature	32° to 122°F
Light Bar Tilt	0 to 90° Electric
Light Bar Rotation	355° Electric
Stabiliser Supports	4 x Manual

BATTERY

Battery	14.4kWh Deep Cycle Gel
Run Time	56 hours
Solar	1.78kWp
Solar Tilt	30°
Solar Efficiency	1 hr of sun/3.5 hrs of light

UNIT INFORMATION

Dimensions (Transport)	144" x 88" x 115" (LxWxH)
Dimensions (Deployed)	142" x 172" x 382" (LxWxH)
Weight	4,189lbs
Trailer Type	Single Axle
Security	Wheel/hitch locks, wheel clamp, security wheel nuts

GPUSA-GP65K-Urban-V4-1125

